



www.EntraPASS.com / 8641 S. Warhawk Rd., Conifer, CO 80433 - Tel: 303-670-1099 - Email: Patrick.McAllister@EntrapASS.com



SECURITRON GL1

**Electromechanical Gate Solution Offers
One Ton of Holding Power**



GL1-FL	Gate Lock, 12/24VDC, Standard Fail Locked
GL1-FS	Gate Lock, 12/24VDC, Standard Fail Safe
GL1-FLM	Gate Lock, 12/24VDC, Monitored Fail Locked
GL1-FSM	Gate Lock, 12/24VDC, Monitored Fail Safe
GMC	Gate Lock Mortise Cylinder (FL Models Only)

Swinging Gates



Sliding Vehicle Gates



Stock Gates



Interior Cribbs



Remote Field Gates





GL1 Electromechanical Gate Lock

GL1

Electromechanical Gate Lock

PRODUCT FEATURES

- 2,000 lbs holding force
- Operates under preload up to 100 lbs
- Automatic dual voltage - no field adjustment required
- Accepts a standard mortise cylinder with Adams Rite MS cam for manual key override (*not included, see spacer guide below*)
- Self-aligning receiver (+/- 1/2" horizontally) helps compensate for gate misalignment and sag
- Tamper resistant cast housing
- Optional latch status monitor
- Surface mount
- MagnaCare® Lifetime Replacement No Fault Warranty

Specifications

Patent: 8,047,582

Holding Force

- 2,000 lbs [907kg]

Dimensions

2-3/4"L x 7-1/4"W x 3-1/4"D

Electrical

- 12 Volts Initial (Peak): (~1.0 sec.) @ 870mA - Reduced: 290mA Power
- Consumption: 3.5 Watts
- 24 Volts Initial (Peak): (~1.0 sec.) @ 720mA - Reduced: 170mA Power
- Consumption: 4.1 Watts

Operating temperature

- -58 to +167F [-50 to +75C] Indoor or outdoor use

Shipping Weight

- 6 lbs [2.72kg]

2,000 lbs Holding Force

100 lbs of Preload


Key Override Ready

Automatic Dual Voltage


Flex-Mount Gate Lock Bracket Kits (FMK)

Bracket Kits Extend Access Control to Gates and Fences.

The FMK Flex-Mount Bracket System is an intuitive set of mounting brackets designed exclusively for use with the the M62FG Magnalock® and GL1 Gate Lock. Pre-formed post channels and plates of varying lengths make it easy for you to assemble a professional looking, high-security gate lock mounting platform in minutes, without special tools.



GL1 with FMK-SL for sliding gates



GL1 with FMK-SW for swinging gates

Cylinder Length	Spacer Required
1"	1/4"
1-1/8"	3/8"
1-1/4"	1/2"