



# MiniProx® Reader

125 kHz Proximity

Mullion Mount Proximity Card Reader • 5365 (Wiegand), 5368 (Clock-and-Data)

[www.TURNSTILES.us](http://www.TURNSTILES.us)



**ACCESS** reliability.

## Application

The MiniProx® proximity card reader's potted electronics enhance the security of the reader. The slim, attractive design is ideal for indoor or outdoor mounting.

## Features

- ▶ Accepts 5 to 16 volts, meeting most voltage requirements.
- ▶ Available with Wiegand or Clock-and-data interface.
- ▶ Allows easy upgrade from magstripe to a proximity reader; no rewiring or pulling of new cable required.
- ▶ Offers high reliability, consistent read-range and low power consumption in an easy-to-install package.
- ▶ Mounts directly onto metal with no change in read range performance.
- ▶ Provides multicolor LED, compatibility with all standard access control systems and internal or host control of LED and beeper.
- ▶ Includes multilingual installation manual.



8641 S. Warhawk Rd. Conifer, CO 80433  
(303) 670-1099 x11 (303) 679-8949 fax  
[Patrick.McAllister@TURNSTILES.us](mailto:Patrick.McAllister@TURNSTILES.us)



## Features

**Mounting** Unobtrusive design mounts directly onto metal including door Mullions.

**Hazardous Location MiniProx® Reader Mounting** Designed to mount onto a junction box included with each reader. The junction box is attached to an appropriate surface location utilizing four holes.

**Audiovisual Indication** When a proximity card is presented to the reader, the red LED flashes green and the beeper sounds. The multicolor LED and beeper can also be controlled individually by the host system.

**Diagnostics** On reader power-up, an internal self-test routine checks and verifies the setup configuration, determines the internal or external control of the LED and beeper, and initializes reader operation. An additional external loop-back test allows for the reader outputs and inputs to be verified without the use of additional test equipment.

**Indoor/outdoor Design** Sealed in a rugged, weatherized polycarbonate enclosure designed to withstand harsh environments, providing reliable performance and a high degree of vandal resistance.

**Easily Interfaced** Wiegand output model interfaces with all existing Wiegand protocol access control systems. Clock-and-Data (magnetic stripe) model interfaces with most systems that accept magnetic stripe readers.

**Security** Recognizes card formats up to 85 bits, with over 137 billion unique codes.

**Warranty** Lifetime warranty against defects in materials and workmanship (see complete sales policy for details).

**Part Numbers** Base Part No.: 5365 Wiegand interface  
Base Part No.: 5368 Clock-and-data interface  
Description: Tri-State LED, Internal beeper on Options:  
• CLASSIC series cover in white, beige, charcoal gray, or black (or)  
• Designer series cover in white, wave blue, charcoal gray, or black  
• LED and beeper operation  
• custom label  
\* Hazardous Location MiniProx® only available with terminal strip.

(Please see "How to Order Guide" for a description of the options and associated part numbers.)

Hazardous Location MiniProx shown with incorporated junction box rated for use in hazardous locations.



## Specifications

### Typical Maximum\* Read Range

ProxCard® II card - up to 5.5" (14 cm)  
ISOProx® II card - up to 5" (12.7 cm)  
DuoProx® II card - up to 5" (12.7 cm)  
Smart ISOProx®/DuoProx® cards - up to 5" (12.7 cm)  
Proximity & MIFARE® card - up to 5" (12.7 cm)  
ProxCard® Plus card - up to 2" (5.1 cm)  
ProxKey® II keyfob - up to 2" (5.1 cm)  
MicroProx® Tag - up to 2.5" (6.4 cm)  
\*Depending on local installation conditions.

### Dimensions:

6.0" x 1.7" x 1.0"  
(15.2 x 4.3 x 2.54 cm)

**Material:** Polycarbonate UL 94

### Power supply:

Standard MiniProx: 5-16 VDC  
Haz. Loc. MiniProx: 5-16 VDC  
Linear power supplies are recommended.

### Current requirements:

Max Average 30 mA  
Typ Peak: 75 mA

### Operating temperature:

-22° to 150° F (-30° to 65° C)

### Operating humidity:

0-95% relative humidity non-condensing

### Weight:

With terminal strip: 3.5 oz. (99 g)  
With pigtail: 3.8 oz. (108 g)  
Haz. Loc. MiniProx: 3.8 oz. (108 g)

**Transmit frequency:** 125 kHz


**Excite frequency:** 125 kHz

### Cable distance:

Wiegand interface: 500 feet (150 m)  
Clock-and-data interface: 50 feet (15 m)  
Recommended cable is ALPHA 1295 (22 AWG) 5 conductor minimum stranded with overall shield or equivalent. Additional conductors may be required for LED or beeper control.

### Certifications:

Canada/UL 294 Listed: Access Control System Units  
Canada/UL 1604 Listed (with Haz. Loc. junction box only):  
Hazardous Locations Class I, Div. 2, Groups A,B,C,D.  
FCC Certification, United States, Canada Certification  
EU and CB Scheme Electrical Safety (EN60950 and IEC60950  
ITE Electrical Safety) Fifteen EU Countries under the R&TTE  
Directive (EN 300 330 - SRD, and ETS 300 683 - EMC), CE  
Mark, Australia C-Tick, New Zealand



MKT-MINIprox-DS-EN

**ACCESS** experience.



**www.TURNSTILES.us**

8641 S. Warhawk Rd. Conifer, CO 80433  
(303) 670-1099 x11 (303) 679-8949 fax  
Patrick.McAllister@TURNSTILES.us