





## 5KVA / 4000 WATT UPS

### UPS Network Management Card



#### Communications & Management

##### Protocols

HTTP, HTTPS, IPv4, IPv6, NTP, SMTP, SNMP v1, SNMP v2c, SNMP v3, SSH V1, SSH V2, SSL, TCP/IP, Telnet

##### Network Interface Connections

RJ-45 10/100 Base-T

##### Authentication

Radius

#### Physical

Net Weight - 0.20 lbs. (0.09 kg)

Maximum Height - 1.50 inches (38 mm)

Maximum Width - 4.75 inches (121 mm)

Maximum Depth - 4.50 inches (114 mm)

Shipping Weight - 0.75 lbs. (0.34 kg)

Shipping Height - 2.00 inches (51 mm)

Shipping Width - 9.25 inches (235 mm)

Shipping Depth - 6.25 inches (159 mm)

#### Environmental

Operating Environment - 32 - 113 °F (0 - 45 °C)

Storage Temperature - 23 - 113 °F (-5 - 45 °C)

Operating Relative Humidity - 0 - 95%

Storage Relative Humidity - 0 - 95%

Operating Elevation - 0-10000 feet

Storage Elevation - 0-15000 feet

#### Conformance

##### Regulatory Approvals

AS/NZS 3548 (C-Tick) Class A, EN 55022 Class A, EN 55024, FCC Part 15 Class A, GOST, ICES-003, VCCI Class A

##### Standard Warranty

2 years repair or replace

#### Sustainable Offer Status

RoHS Compliant

REACH: Contains No SVHCs

Battery Directive - Compliant

Battery Notes - Contains Lithium Battery