wwww.EntraPASS.com / 8641 S. Warhawk Rd., Conifer, CO 80433 - Tel: 303-670-1099 - Email: Patrick.McAllister@EntraPASS.com

5KVA / 4000 WATT UPS

Smart-UPS

Smart-UPS ,4000 Watts /5000 VA,
Input 208V /Output 208V,
Interface Port DB-9 RS-232,
SmartSlot,
Rack Height 5 U

Includes: CD with software, Rack Mounting support rails, Smart UPS signalling RS-232 cable, User Manual, Web/SNMP Management Card
Standard Lead Time: Usually Ships within 3 Weeks

Output
Output Power Capacity - 4000 Watts / 5000 VA
Max Configurable Power - 4000 Watts / 5000 VA
Nominal Output Voltage - 208V
Output Voltage Distortion - Less than 5% at full
Output Frequency (sync to mains)
47 - 53 Hz for 50 Hz nominal, 57-63Hz for 60 Hz
Output Connections

(2) NEMA L6-20R

(2) NEMA L6-30R

Input
Nominal Input Voltage - 208V
Input Frequency - 50/60 Hz +/- 5 Hz
Input Connections

NEMA L6-30P

Cord Length - 8 feet (2.44 meters)
Input voltage range main - 141 - 255V
Input voltage adjustable range - 131 - 268V

www.EntraPASS.com
8641 S. Warhawk Rd., Conifer, CO 80433 - Tel: 303-670-1099 - Email: Patrick.McAllister@EntraPASS.com

wwww.EntraPASS.com / 8641 S. Warhawk Rd., Conifer, CO 80433 - Tel: 303-670-1099 - Email: Patrick.McAllister@EntraPASS.com

5KVA / 4000 WATT UPS

Batteries & Runtime

Batteries & Runtime

Battery Volt-Amp-Hour Capacity
816
Battery Type
Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Battery mounting
--
Expected Battery Life (years)
3 - 5
RBC™ Quantity
1

Physical

Net Weight
53.40 lbs. (24.27 kg)
Maximum Height
6.80 inches (173 mm)
Maximum Width
5.60 inches (142 mm)
Maximum Depth
7.20 inches (183 mm)
Shipping Weight
58.70 lbs. (26.68 kg)
Shipping Width
11.60 inches (295 mm)
Shipping Height
10.90 inches (277 mm)
Shipping Depth
21.20 inches (538 mm)
Color
Black
Units per Pallet
18.00

Environmental

Operating Environment
32 - 104 °F (0 - 40 °C)
Operating Relative Humidity
0 - 95%
Operating Elevation
0-10000 feet (0-3000 meters)
Storage Temperature
5 - 113 °F (-15 - 45 °C)
Storage Relative Humidity
0 - 95%
Storage Elevation
0-50000 feet (0-15000 meters)

Conformance

Standard Warranty
1 year repair or replace

Sustainable Offer Status

RoHS
Compliant
REACH
REACH: Contains No SVHCs
PEP
Available in Documentation tab
EOLI
Available in Documentation tab

*Except where noted, all prices are Estimated Resale Price (ERP) - Without Tax/VAT. Pricing in other locations and sites may vary.

www.EntraPASS.com
8641 S. Warhawk Rd., Conifer, CO 80433 - Tel: 303-670-1099 - Email: Patrick.McAllister@EntraPASS.com

wwww.EntraPASS.com / 8641 S. Warhawk Rd., Conifer, CO 80433 - Tel: 303-670-1099 - Email: Patrick.McAllister@EntraPASS.com

5KVA / 4000 WATT UPS

UPS Network Management Card

Communications & Management
Protocols

HTTP, HTTPS, IPv4, IPv6, NTP, SMTP, SNMP v1, SNMP v2c, SNMP v3, SSH V1, SSH V2, SSL, TCP/IP, Telnet

Network Interface Connections
RJ-45 10/100 Base-T

Authentication
Radius

Physical
Net Weight - 0.20 lbs. (0.09 kg)

Maximum Height - 1.50 inches (38 mm)

Maximum Width - 4.75 inches (121 mm)

Maximum Depth - 4.50 inches (114 mm)

Shipping Weight - 0.75 lbs. (0.34 kg)

Shipping Height - 2.00 inches (51 mm)

Shipping Width - 9.25 inches (235 mm)

Shipping Depth - 6.25 inches (159 mm)

Environmental
Operating Environment - 32 - 113 °F (0 - 45 °C)

Storage Temperature - 23 - 113 °F (-5 - 45 °C)

Operating Relative Humidity - 0 - 95%

Storage Relative Humidity - 0 - 95%

Operating Elevation - 0-10000 feet

Storage Elevation - 0-15000 feet

Conformance
Regulatory Approvals
AS/NZS 3548 (C-Tick) Class A, EN 55022 Class A, EN 55024, FCC Part 15 Class A, GOST, ICES-003, VCCI Class A

Standard Warranty
2 years repair or replace

Sustainable Offer Status
RoHS Compliant

REACH: Contains No SVHCs

Battery Directive - Compliant

Battery Notes - Contains Lithium Battery