

Entry Pass

Stand-Alone Door Controller



Features That Make a Difference:

- Simple and convenient
- Save up to 8 configurations (door access schedule, door unlock schedules, etc.) on a USB to load on other ioPass SA-550 units
- Use card, PIN or both
- Program controller from the keypad
- Integrates with an optional external ioProx reader
- Store up to 1,000 users
- Audit trail on last 3,500 transactions with time stamp
- 6 language selectable user interface: English, French, Spanish, German, Dutch and Italian
- Program 24 recurring holidays (January 1 and December 25 pre-set) per controller
- 24 non-recurring holidays per controller
- 4 door access schedules and 1 door unlock schedule per controller

Stands Alone In The Field

Perfect for smaller applications such as convenience stores, storage rooms or parking lots, the SA-550 is a fully self-contained stand-alone controller with an integrated ioProx 26-bit Wiegand proximity card reader. It can store up to 1,000 users and is programmed directly from the keypad. The controller can define access levels, unlock schedules and holidays. Audit trail with time stamp is also available for up to 3,500 transactions. All commands are displayed on the 16-character, 2-line LCD.

Upload, Download And Backup

The door configuration, card database and events can be downloaded to a USB key for backup. The SA-550 controllers can support up to 8 different door configurations (door access schedules, door unlock schedules, etc.). The door configuration data can be transferred to any number of SA-550 controllers via a USB key.

Optional External Reader

For added convenience and security, the SA-550 may be integrated with an external ioProx reader. This will allow the controller to remain on the secure side of door. Or it allows the weather-resistant external reader to be used outside, even in cold environments.

Invalid Password Lockout

To prevent unauthorized persons from gaining password entry by trial and error the system activates an alarm relay and/or automatically deletes the card number after five tries once the option is selected in the system.

Door Relay Module

The ioPass relay module is separate from the unit and can be concealed inside a wall or ceiling.

Specifications

Typical Read Range	Up to 10 cm (4 in)
Input Voltage	12 VDC
Current DC Maximum	300mA
Display	16 characters, 2 lines, LCD with backlight
Languages Programmable from Keypad	English, French, Spanish, German, Dutch, Italian
Dimensions (H x W x D)	15 x 9.5 x 4 cm (5.9 x 3.8 x 1.6 in)
Weight	380 g (13.5 oz)
Color	Black
Case Material	ABS (UL 94V-0)
LED Indicator	Bicolor (green/red)
Sounder	Piezoelectric
Operating Temperature	0°C to 50°C (32°F to 122°F)
Operating Humidity	5% to 95% (relative humidity non-condensing)
Maximum Distance Between:	
Controller and Proximity Reader	150 m (500 ft), 2 twisted pairs, solid conductor #22AWG unshielded
Controller and Relay Module	150 m (500 ft), 2 twisted pairs, solid conductor #22AWG unshielded
Relay Module and Power Supply	150 m (500 ft), 1 pair, solid conductor #18AWG unshielded
Recommended Power Supply	12 VDC, 1A
Door Contact Input	NO or NC selectable
Request-to-Exit Input	NO or NC selectable
Relay Output (Strike Relay, Alarm Relay, Relay-1)	Form C, NO and NC, 3A, 24 VDC
Strike Relay Timer	1 to 255 sec
Alarm Relay Timer	1 to 255 sec
Relay-1 Timer	1 to 255 sec
Door Ajar Timer	1 to 255 sec
Audit Trail	Last 3,500 transactions with time stamp
Compatible Cards	ioProx cards P10SHL, P20DYE, P30DMG, P40KEY and P50TAG
User Capacity	Store up to 1,000 user records
Certifications	CE, FCC, UL294 and ICES-003

