

## PB24vDC – Push-Button Relay Module



Plastic  
Operator

Color Red

Action  
Momentary



Metallic  
Enclosure

Conduit Size 3/4 Inch NPT

Number of  
Holes 1



### Overview

Model 6062 programmable timer is suitable for many functions that require a timed operation e.g. Access Control Applications, Siren/Bell Cut Off Module, Dialer Delay, Guard Tour Supervisory Timer, etc. Some optional functions include: One Shot, Delayed Release, Delayed Operate, Delayed Pulse and Pulsar/Flasher. A new feature has been added which provides a momentary relay activation at the end of a desired timing cycle. This feature eliminates the need for having to use two (2) timers to achieve this function. Another new feature will cancel (interrupt) timing cycle and reset timer if desired

### Specifications

- 12VDC or 24VDC selectable operation.
  - Accurate time range adjustment  
1 sec to 60 min.
  - LED indicates relay is energized.
  - Form "C" relay contacts are 8 AMP at 120VAC/28VDC.
- Current Draw: Stand-by 3mA, Relay Energized 40mA.
  - Triggers via positive DC (+) voltage, dry contact closure, or removal of contact closure.
- Selectable relay activation at the start or end of the timing cycle.
- One (1) second momentary relay activation at the end of the timing cycle (eliminates the need to use two (2) timers for

### Board

- Dimensions (approximate):  
2.5"W x 3"L x 0.75"H